


LIFTINGS

Country	GABON
Terminal	FSO Fernan Vaz is operated by Perenco Oil & Gas Gabon
Location	Offshore around 10 miles west of Port Gentil
Loading Restriction	Terminal accepts VLCC 1 st and 2 nd port up to 325k DWT
Loading Rate	48,000 bbl/hour via Loading Buoy
Cargo Size	450,000 bbl to 1,050,000 bbl
Note	New Loading Buoy operational since July 2015



CRUDE OIL CHARACTERISTICS

General	Oguendjo is a low sulfur, medium gravity, naphthenic paraffinic Crude Oil, with low pour point, with Mid-distillates of very good cold properties.
Naphtha	Good yield suited for reforming feedstock with a good N+2A.
Kerosene	12 LV% of excellent feedstock for Jet Fuel, with high smoke point and aniline point.
Gas Oil	19% LV% with high cetane index and very good combustion properties; good pour point and low sulphur content.
VGO	High yield of thermal and catalytic feedstock.
Residue	Suitable for Asphalt Cement bases.



OGUENDJO

API Gravity	31.86
Density 15°C kg/l	0.8657
Sulfur WT%	0.959
Nitrogen ppm	1380
RVP kPa	30.7
Pour Point °C	6
TAN mgKOH/g	0.76
Viscosity 40°C cSt	9.1
Viscosity 50°C cSt	6.7
Vanadium ppm	15
Nickel ppm	30

Perenco makes no representations or warranties express or implied, regarding the accuracy, adequacy, reasonableness or completeness of the information, assumptions or analysis contained herein or in any supplemental materials, and Perenco accepts no liability in connection therewith. This information on the crude oil presented here was prepared by Perenco. It is for your private information and we are not soliciting or suggesting any action based upon it. The actual yields and qualities of production may vary and no representation or warranty, expressed or implied, is made as to the accuracy or completeness of the information in this brochure or any accompanying crude assay.

